LONSEAL® FLOORING

LONSTAGE® UV

Striking and Bold

LONSTAGE UV has the same bold and slick look as our Lonmetro but a smoother surface. Its ultra-clean style means that Lonstage UV is suitable for showrooms and "showplace" spaces. Recommended for interior use only, and should not be used where subject to extreme mechanical use. Ideal for stages, entertainment and dance studios.

FEATURES (data shown is nominal):

Roll Width: 6 ft. (1.8 m) Roll Length: 60 ft. (18.3 m)

Overall Thickness: 0.080 in. (2.0 mm) Wear Layer Thickness: 0.018 in. (0.45 mm)

Weight: 0.7 lbs./sq. ft. (3.4 kg/m²)

ASTM F1303 CLASSIFICATION:

Type I, Grade 1, Class B, Commercial Use

CERTIFIED:

FloorScore®

EXCLUSIVE LONSEAL FORMULATIONS:

GreenAir® & GreenMedic®

LEEDv4/4.1 CONTRIBUTION B & C Interiors:

Environmental Product Declarations Option 1 Sourcing of Raw Materials Option 2

Low-Emitting Materials

Pre-Consumer (Post-Industrial) Recycled Content

* Due to the light color of #\$100 Shiny White, more frequent maintenance procedures are necessary to ensure a long-lasting installation. In addition, areas of prolonged UV exposure should be avoided to prevent unwanted discoloration of the flooring.

WARNING: Cancer and Reproductive Harmwww.P65Warnings.ca.gov



