LONSEAL® FLOORING

LONWOOD® DAKOTA Topseal

Oak, Quarter Sawn, Timber Classic

LONWOOD DAKOTA is a slightly textured sheet that evokes the open grain of oak and the nuance of knot-free, quarter-sawn plank. Ideal for corporate, healthcare, retail and hospitality applications. Lonwood Dakota now comes standard with Lonseal's exclusive Topseal formulation. Topseal is a factory-applied urethane finish that protects the floor, reduces scuffing and simplifies routine maintenance. Topseal wear layer extends the life of the flooring by protecting it from wear due to staining, soiling and scuffing.

This product contains partial "boards" at both edges. This selvage should be removed to assure an aesthetically pleasing transition from sheet to sheet. The selvage width can vary depending on the lot.

FEATURES (data shown is nominal):

Roll Width: 6 ft. (1.8 m) Roll Length: 60 ft. (18.3 m)

Overall Thickness: 0.080 in. (2.0 mm) Wear Layer Thickness: 0.020 in. (0.5 mm) Weight: 0.6 lbs./sq. ft. (3.1 kg/m²)

ASTM F1303 CLASSIFICATION:
Type I, Grade 1, Class B, Commercial Use

CERTIFIED: FloorScore®

EXCLUSIVE LONSEAL FORMULATIONS: Topseal, GreenAir® & GreenMedic®

LEEDv4/4.1 CONTRIBUTION B & C Interiors: Environmental Product Declarations Option 1 Sourcing of Raw Materials Option 2 Low-Emitting Materials Pre-Consumer (Post-Industrial) Recycled Content



