

INSTALLER'S CHECKLIST

INTERIOR INSTALLATIONS:

- Premium Bond #755 Sheet Vinyl Adhesive** (Field)
 - #650 Two-Component, Solvent-Free Epoxy Adhesive** (Extreme use)
 - #400 Contact Adhesive** (Flash coving and stairs)
 - Double Face Tape** (Under seams)
 - Lonsealer** (Chemical welds)
- OR
- Welding Thread** (Heat welds)
 - ZZ65 Urethane Nozzle** (For use with all urethane-finished products, e.g. Topseal)

ELEVATOR INSTALLATIONS:

- #650 Two-Component, Solvent-Free Epoxy Adhesive**
- Welding Thread** (Heat welds)
- ZZ65 Urethane Nozzle** (For use with all urethane-finished products, e.g. Topseal)

FIXTURE INSTALLATIONS:

- #400 Contact Adhesive**
- Welding Thread** (Heat welds)
- ZZ65 Urethane Nozzle** (For use with all urethane-finished products, e.g. Topseal)

ADHESIVES AND SUNDRIES:

- Premium Bond #755 Sheet Vinyl Adhesive:** 1 and 3.5 gal. units (See table below)
- #650 Two-Component, Solvent-Free Epoxy Adhesive:** 1 gal. unit (See table below)
- #400 Contact Adhesive:** 1 gal. unit (See table below)
- Double Face Tape:** Roll (2" wide x 60 ft. length)
- Lonsealer:** 4.7 oz. tube (Appx. 200 linear ft.)
- Welding Thread:** 100 ft. minimum or 1 spool @ 500 ft.
- Lexel® Clear Sealant:** 10.5 oz. cartridge (Appx. 26 LF @ 1/4")

MAINTENANCE* :

- Microfiber Dust Mop** (for use prior to wet mopping or general dusting)
- Microfiber Wet Mop** (for wet mopping or finish application)
- Neutral pH Cleaner** (for daily maintenance)
- Sheet Vinyl Floor Finish** (for unfinished flooring)
- Sheet Vinyl Floor Stripper** (for stripping finishes from unfinished flooring)
- Red Buffing Pad** (for cleaning Topseal flooring)
- Blue Scrubbing Pad** (for cleaning unfinished flooring)
- Brown Stripping Pad** (for stripping finishes from unfinished flooring)
- Spray Buff** (for Lonstage UV and Lonmetro UV)
- TASKI Contact Pad** (for Lonstage UV and Lonmetro UV)

*Lonseal does not stock maintenance products. Please refer to the appropriate **Maintenance Guide** at www.lonseal.com for more information.

APPROXIMATE SPREAD RATE TABLE:

Premium Bond #755 Sheet Vinyl Adhesive	U-notch Trowel	Square-notch Trowel (sport flooring only)	Nap Roller** (non-porous surfaces)
	1/16" x 1/32" x 1/32"	1/16" x 1/16" x 1/16"	3/8"
Approx. Spread Rate*	185 – 245 sq. ft./gal.	140 – 160 sq. ft./gal.	180 – 200 sq. ft./gal.
Open Time†	15 – 30 minutes	15 – 30 minutes	15 – 30 minutes
Working Time‡	1 hour	1 hour	1 hour
#400 contact Adhesive			
	Nap Roller**	Disposable Paint Brush**	
	3/8"	Clean/New	
Approx. Spread Rate*	150 – 200 sq. ft./gal.	150 – 200 sq. ft./gal.	
Open Time†	3 – 15 minutes	3 – 15 minutes	
Working Time‡	0 minutes***	0 minutes***	
#650 Two-Component, Solvent-Free Epoxy Adhesive			
	U-notch Trowel		
	1/16" x 1/32" x 1/32"		
Approx. Spread Rate*	170 – 225 sq. ft./gal.		
Open Time†	Up to 15 minutes		
Working Time‡	Up to 15 minutes		

Note: Trowel sizes listed are by width/depth/space. All information provided in the above table will vary depending on the job site conditions, including temperature, humidity, substrate porosity, and applicator.

*Actual job site spread rate will vary depending on the substrate conditions.

†OPEN TIME: Waiting time required before placing the flooring material into the adhesive.

‡WORKING TIME: Amount of time for the adhesive to accept the flooring material after being applied to the substrate.

**Spread rate shown is per surface. The substrate and back of the flooring are considered two separate surfaces when determining quantity of adhesive necessary for the installation.

***Due to the high initial tack of the #400, once the flooring is placed into the adhesive after allowing for adequate open time, it will not be able to be repositioned.

Disclaimer: This document is only intended to help customers ensure they purchase all necessary products for a successful installation. Complete installation requirements and recommendations may be found in the **Technical Manual for Interior Flooring Products** available at www.lonseal.com.