

ATTENTION: Always refer to the **Technical Manual for Interior Flooring Products** for complete installation information prior to using this product. Lonseal reserves the right to change our products' design, material, and/or to improve products or processes at any time without notice. Installation procedures and use of Lonseal adhesives must be in strict accordance with Lonseal's technical documents for warranty terms to be valid. **Please review the website for the most current technical information.**

DESCRIPTION: A multi-purpose double coated cloth tape for general mounting and holding. Specially designed for the convention/trade show industry, as well as for temporary flooring installations

USE: For bonding Lonseal flooring to an approved substrate.

ADVANTAGES:

- ▶ Designed for easy removal of temporary floors.
- ▶ Cloth reinforcement
- ▶ Low VOC content

APPLICATION:

1. Apply Show Tape to the back of the flooring material, leaving the blue liner intact. To ensure proper adhesion, full coverage of tape to the back of the material is recommended.
2. Place and align the flooring before removing the liner.
3. Beginning at the edge of the installation area, tube (fold the flooring over itself lengthwise) the sheet towards the center of the installation. Take care, and keep the radius large when folding the material. Failure to do so could result in damage to the flooring, and visual imperfections may appear on the surface.
4. Begin pulling the liner off the tape at an angle until a significant portion of the tape has been exposed.
5. Slowly un-tube the material and apply pressure from the center out to the edge to reduce the chance of air bubbles.
6. Tube the other side of the sheet towards the edge of the installation area, and repeat steps 5 and 6.
7. Continue until the area is fully adhered. To ensure the best adhesion, roll the material using a minimum 75 lb., three-section roller in both directions. At a minimum, it is recommended to use a J-roller.
8. Avoid peeling or prying of the edges to ensure the best bond.

CLEAN UP: Dispose of the liner, and any scraps, in an environmentally safe manner.

LIMITATIONS: For interior, temporary applications only. Protect from freezing.

PHYSICAL PROPERTIES:

- ▶ **Color:** Natural
- ▶ **Adhesive:** Rubber
- ▶ **Backing:** Blue LDPE
- ▶ **Thickness:** 0.011" (0.28 mm)
- ▶ **Tensile Strength:** 20 lbs./in. (35.03 N/cm)
- ▶ **Adhesion - Steel:** 40 oz./in. (4.38 N/cm)
- ▶ **VOC:** <1 g/L
- ▶ **Shelf Life:** Two years from date of manufacture, when stored at 77 °F (25.0 °C).
- ▶ **Storage Conditions:** 60 °F – 80 °F (15.6 °C – 26.7 °C), 40 – 60% humidity; keep dry and out of direct sunlight.
- ▶ **Application Conditions:** 65 °F – 85 °F (18.3 °C – 29.4 °C)
- ▶ **Available Sizes:** 2" x 25 yds.
- ▶ **Concrete Requirements:** 5 lbs./1,000 ft²/24 h max. MVER; 75% max. RH; 9 pH max.
- ▶ **Coverage:** 75 linear feet per roll