## LONSEAL® FLOORING

## **LONMOIRE TOPSEAL**

Antique Elegance in a Modern World Phthalate Free

LONMOIRE TOPSEAL's wood grain pattern has the characteristics of watery waves of lines. This ripple design was once coveted by queens. It distinguishes the centuries-old pattern that now gives everyday commercial spaces a genteel touch. Lonmoire is **PHTHALATE FREE** and also features Lonseal's exclusive Topseal formulation. Topseal is a factory-applied urethane finish that protects the floor, reduces scuffing and simplifies routine maintenance. Topseal is applied in a 30-micron wear layer and extends the life of the flooring by protecting it from wear due to staining, soiling and scuffing.

FEATURES (data shown is nominal):

Roll Width: 6 ft. (1.8 m) Roll Length: 60 ft. (18.3 m)

Overall Thickness: 0.080 in. (2.0 mm) Wear Layer Thickness: 0.020 in. (0.5 mm) Weight: 0.7 lbs./sq. ft., 240 lbs./roll

ASTM F1303 CLASSIFICATION:
Type I, Grade 1, Class B, Commercial Use

CERTIFIED: FloorScore®

EXCLUSIVE LONSEAL® FORMULATIONS: GreenAir® & GreenMedic®

LEEDv4 CONTRIBUTION Building & Construction Interiors: Environmental Product Declarations Option 1 Sourcing of Raw Materials Option 2 Low-Emitting Materials



