LONSEAL® FLOORING

LONMAT® UV & XL

Meets MIL-DTL-15562G. TYPE I & TYPE II

LONMAT UV features an innovative UV-cured urethane finish that simplifies maintenance; this durable, marbleized, fire-retardant, electrically-insulating surface has been the foundation of countless naval vessels' high-voltage areas for decades. Lonmat UV meets the U. S. Military and NATO Switchboard Matting, MIL-DTL-15562G, TYPE I specifications for flooring matting products which insulate workers from electrocution by interrupting the path to ground. Type I Switchboard Matting is often used on ship decking and around electrified equipment where maintenance and operational personal work, and is known for its water-tight integrity with heat-welded seams.

LONMAT XL is a durable, marbleized, fire-retardant, electrically-insulating surface has been the foundation of countless naval vessels' high-voltage areas for decades. Lonmat XL is tested to the requirements of MIL-DTL-15562G, TYPE II for military switchboard matting. It is an electrical-grade matting product which insulates workers from electrocution by interrupting the path to ground. Type II Switchboard Matting is often used on ship decking and around electrified equipment where maintenance and operational personal work. Lonmat XL is available exclusively in 8' width and only comes in Green Marble.

LONMAT UV FEATURES (data shown is nominal):
Roll size 3': 3 ft. (0.9 m) wide x 75' (22.9 m) length
Roll size 6': 6 ft. (1.8 m) wide x 30' (9.1 m) length
Overall Thickness: 0.128 in. (3.2 mm)
Wear Layer Thickness: 0.048 in. (1.2 mm)
Weight: 1.1 lbs./sq. ft. (5.1 kg/m²)

LONMAT XL FEATURES (data shown is nominal):
Roll Width: 8 ft. (2.4 m)
Roll Length: 40 ft. (12.2 m)
Overall Thickness: 0.128 in. (3.2 mm)
Wear Layer Thickness: 0.064 in. (1.6 mm)
Weight: 1.0 lbs./sq. ft. (5.0 kg/m²)

* Please note that all colors for Lonmat UV are available in either 3 foot (0.914 m) x 75' (22.86 m) length and 6 foot (1.83 m) width x 30' (9.14 m) length rolls.





