LONSEAL®

LONCOURT® UV

Durable, Functional, and Resists Indentation

LONCOURT UV pairs the durability and aesthetics of the original Loncourt flooring with a factory-applied urethane finish for easier maintenance. This reduces the lifetime cost of the floor by eliminating the need to reapply coats of finish over time.

FEATURES (data shown is nominal): Roll Width: 6 ft. (1.8 m) Roll Length: 50 ft. (15.2 m) Overall Thickness: 0.192 in. (4.8 mm) Wear Layer Thickness: 0.020 in. (0.5 mm) Weight: 1.6 lbs./sq. ft. (7.9 kg/m²)

MEETS NCAA: Basketball Rebound Requirements (49" - 54")

ASTM F1303 CLASSIFICATION: Type I, Grade 1, Class B, Commercial Use

CERTIFIED: FloorScore®

EXCLUSIVE LONSEAL FORMULATIONS: GreenAir[®] & GreenMedic[®]

LEEDv4/4.1 CONTRIBUTION B & C Interiors: Environmental Product Declarations Option 1 Sourcing of Raw Materials Option 2 Low-Emitting Materials Pre-Consumer (Post-Industrial) Recycled Content

WARNING: Cancer and Reproductive Harmwww.P65Warnings.ca.gov





CT838UV Buckwheat



928 E. 238[™] STREET, CARSON, CA, 90745

310.830.7111

WWW.LONSEAL.COM

Printing limitations may not represent the true color of the product. If color match is critical, please call us to request a sample. For the most up-to-date color choices, go to LONSEAL.COM.