

Lonseal, Inc. and Spray-Lock, Inc. have completed compatibility testing of Spray-Lock® 3500 Spray Adhesive with Lonseal sheet vinyl flooring, and the Spray-Lock® 3500 is approved for use in commercial, interior applications.

If specified for installation areas incurring heavy static or dynamic loads, such as patient beds, then the Spray-Lock® 3500 would be the sole adhesive used, instead of any Lonseal branded adhesives.

**Disclaimer:** Use of Spray-lock® 3500 with Lonseal sheet vinyl flooring is subject to the Spray-Lock, Inc. limited warranty. This includes support for product performance claims and provisions on warranty coverage. Lonseal does not sell or market Spray-Lock® products, nor is Spray-Lock® 3500 covered by Lonseal's warranty.

Application will be per Spray-Lock® requirements, per their most current technical documentation. Coverage is 150 – 185 sq. ft. per 22 oz. can.

Spray-Lock® 3500 benefits:

- ▶ Solvent-free and low VOC content (0.020 g/mL)
- ▶ Heat weld the same day
- ▶ Provides immediate shear strength
- ▶ Non-flammable
- ▶ Concrete Moisture Requirements: 98% RH, 8 lbs. MVER, 11 pH

For additional information, assistance, or pricing, please contact Elliot Brown of Spray-Lock, Inc.® at (423) 305-6151, [eabrown@spraylock.com](mailto:eabrown@spraylock.com), or visit [www.spraylock.com](http://www.spraylock.com).

