

Lexel[®]
—elastic sealant—

Lonseal and Sashco, Inc. have completed compatibility testing of Lexel[®] elastic sealant with all interior and exterior Lonseal sheet vinyl flooring products. Lexel is approved by Sashco, Inc. for use with Lonseal flooring products.

Application Preparation: Prior to applying Lexel[®], Sashco recommends removing any dirt or oils with a standard household cleaner and allow ample time to dry. Any loose materials or old caulking should be cut away, and any existing silicone should be completely removed to ensure proper adhesion of Lexel[®].

DISCLAIMER: Use of Lexel[®] elastic sealant with Lonseal vinyl flooring is subject to the Sashco, Inc. Limited Lifetime Warranty (sashco.com/hi/pdfs/Lexel_TechData.pdf). This includes support for product performance claims and provisions on warranty coverage. Lonseal does not sell or market Lexel[®] nor is Lexel covered by Lonseal's warranty.

Lexel[®] elastic sealant product benefits:

- ▶ **Tough:** Lexel[®] survives routine scrubbing with household cleaners, including abrasive cleaners.
- ▶ **Super elastic:** When the surface moves, Lexel[®] moves. No cracking, tearing, or pulling away for a lasting, permanent seal.
- ▶ **Instantly waterproof:** No Waiting and wondering necessary. Lexel[®] can get wet immediately.
- ▶ **Cured sealant is mold and mildew resistant:** With Lexel[®], unsightly and unhealthy growths stay where they belong – in a lab, not on your caulk.
- ▶ **Sticks to wet surfaces:** Dry weather may be days away. Lexel[®] can be applied today.
- ▶ **Ultra Clear Sealant:** In fact, Lexel[®] 19x clearer than silicone. It won't yellow and won't go cloudy.
- ▶ **Won't freeze:** Feel free to leave Lexel[®] in your truck or garage overnight. It'll be fine in the morning.

For additional information and assistance with Lexel[®] elastic sealant, please contact Sashco's customer service at 800-767-5656 or via the web at www.sashco.com

