

LONSEAL[®]

FLOORING

LONSPECK[®] Topseal

High Performance with a Timeless Design

The speckled surface of LONSPECK TOPSEAL easily hides grit and scuffing, while the sanitary seaming contributes to a hygienic environment. The nine therapeutic colors available make Lonspeck an exceptionally flexible option in commercial spaces, including healthcare, offices, education facilities and showrooms. Topseal is a factory-applied urethane finish that protects the floor, reduces scuffing and simplifies routine maintenance. Topseal is applied in a 30-micron wear layer and extends the life of the flooring by protecting it from wear due to staining, soiling and scuffing.

FEATURES *(data shown is nominal):*

Roll Width: 6 ft. (1.8 m)
Roll Length: 60 ft. (18.3 m)
Overall Thickness: 0.080 in. (2.0 mm)
Wear Layer Thickness: 0.028 in. (0.7 mm)
Weight: 0.6 lbs./sq. ft. (3.1 kg/m²)

ASTM F1303 CLASSIFICATION:

Type I, Grade 1, Class B, Commercial Use

MEETS FMVSS 302:

CFR 49 §571.302 Flammability of Interior Materials

CERTIFIED:

FloorScore[®]

EXCLUSIVE LONSEAL FORMULATIONS:

TOPSEAL, GreenAir[®] & GreenMedic[®]

LEEDv4/4.1 CONTRIBUTION B & C Interiors:

Environmental Product Declarations Option 1
Sourcing of Raw Materials Option 2
Low-Emitting Materials

 **WARNING:** Cancer and Reproductive Harm-
www.P65Warnings.ca.gov





SX111
Twilight Zone



SX112
Magnetic Gray



SX113
Rocky Beach



SX114
Tamarind




SX115
Sandstorm




SX116
White Pepper



SX117
Hale Navy



SX118
Vanilla Bean



SX119
Pigeon Gray

