

Lonseal, Inc. and Spray-Lock, Inc.® have completed compatibility testing of Spray-Lock® 3500 with Lonseal sheet vinyl flooring, and the 3500 is approved for use in commercial, interior applications.

If specified for installation areas incurring heavy static or dynamic loads, such as patient beds, then the 3500 would be the sole adhesive used instead of any Lonseal branded adhesives.

Disclaimer: Use of Spray-lock® 3500 with Lonseal sheet vinyl flooring is subject to the Spray-Lock, Inc.® limited warranty. This includes support for product performance claims and provisions on warranty coverage. Lonseal does not sell or market Spray-Lock® products nor is Spray-Lock® 3500 covered by Lonseal's warranty.

Application will be per Spray-Lock® requirements, per their most current technical documentation. Coverage is 150 – 185 sq. ft. per 22 oz. can.

Spray-Lock® 3500 benefits:

- ▶ Solvent-free and low VOC content (0.020 g/mL)
- ▶ Heat weld the same day
- ▶ Provides immediate shear strength
- ▶ Non-flammable
- ▶ Concrete Moisture Requirements: 95% RH, 8 lbs. MVER, 11 pH

For additional information, assistance, or pricing, please contact Larry Moore of Spray-Lock, Inc.® at (479) 631-0148, ldmoore@spraylock.com, or visit www.spraylock.com.

